

Amendments to the Claims: This listing of claims will replace all prior versions, and listings, of claims in the application

Listing of Claims:

1. - 10. (Cancelled)

11. (Currently Amended) A device for monitoring the fluid level of a supply reservoir comprising:

a float including a magnet for actuating a switch or a sensor, wherein the float has a multipart design comprising a first float part and a second float part, wherein the second float part has an upper surface with an annular recess defined in the upper surface, the annular recess configured to receive and support the magnet and the first float part is configured to cover the recess such that the magnet is arranged-encased between the two float parts-in-an encased fashion.

12. (Cancelled)

13. (Currently Amended) The device as claimed in claim 11, wherein the first float part and the second float part are adapted to be locked with each other by ~~means of~~ lock elements.

14. (Previously Presented) The device as claimed in claim 11, wherein the first float part has a stepped through-bore into which the second float part is mounted by means of a press fit.

15. (Currently Amended) The device as claimed in claim 14, wherein the magnet is arranged in ~~an-the~~ annular recess of the second float part, which is covered by a step of the first float part after the two float parts have been fitted together.

16. (Currently Amended) The device as claimed in claim 11, wherein the first float part can be slipped into the second float part, and the magnet is ~~arranged in an annular recess on a top side of the second float part, which is covered~~ by a bottom side of the first float part after the two float parts have been fitted.

17. (Previously Presented) The device as claimed in claim 11, wherein the second float part has a radial recess into which the first float part can be slipped, and projections are provided

at sidewalls of the first float part which allow slipping the first float part in a guided manner into the radial recess of the second float part.

18. (Cancelled)

19. (Previously Presented) The device as claimed in claim 11, wherein the first float part at a bottom side thereof includes a projection which snaps into a recess on a top side of the second float part after the two float parts have been fitted.

20. (Previously Presented) The device as claimed in claim 11, wherein the first float part and the second float part are configured as a foamed plastic part.

21. (Previously Presented) The device as claimed in claim 11, wherein the supply reservoir is part of a hydraulic motor vehicle brake system.

22. (New) The device as claimed in claim 11, wherein the first float part includes a lower surface with an annular recess defined in the lower surface, wherein in an assembled form of the device the annular recess of the first float part and the annular recess of the second float part define a common annular space that is sized to encase the magnet.